


GRAND BANTAM DUAL REAR WHEEL • 11,500 • 12,300 • 14,050 GVW

SPECIFICATIONS //

Rows: 5-6
Passengers: Up to 30
Floor Design: Flat floor
Headroom: 76"
Configurations: School Bus, Multifunction School Activity Bus, or Bus

CHASSIS & ENGINE //

Option A: GM chassis • 12,300 GVW Diesel or 12,300 GVW Gas

Option B: Ford chassis • 11,500 and 14,050 GVW Diesel

FEATURES //

- Big bus features with small bus maneuverability
- ISO 9001:2000 Certified manufacturer
- Totally redesigned to enhance quality and safety
- Optional in-wall rear air conditioning maximizes passenger compartment headroom
- Limited lifetime paint warranty available
- Exclusive 5 year body warranty
- A variety of floor plans allowing flexibility in seating configurations

SPECS

SPECS	FORD 350		FORD E450		GM			
	FGX5WR	FGX6	FGX6WR	CGX5	CGX6	CGS5WR	CGX6WR	
Passenger capacity	14 + 2 WC*	30*	22 + 2 WC*	29*	24*	18 + 2 WC*	20 + 2 WC*	
Interior height at aisle	76.5"	76.5"	76.5"	76.5"	76.5"	76.5"	76.5"	
Interior height at sidewall	72.8"	72.8"	72.8"	72.8"	72.8"	72.8"	72.8"	
Interior width	91"	91"	91"	91"	91"	91"	91"	
Entrance door (w x h)	24" x 78"	24" x 78"	24" x 78"	24" x 78"	24" x 78"	24" x 78"	24" x 78"	
Entrance step from ground	14"	14"	14"	14"	14"	14"	14"	
Emergency door (w x h)	36" x 50"	36" x 50"	36" x 50"	36" x 50"	36" x 50"	36" x 50"	36" x 50"	
Wheelchair lift door (opt.)	42" x 64"	-	42" x 64"	-	-	42" x 64"	42" x 64"	
Overall height	114"	114"	114"	114"	114"	114"	114"	
Overall width	95"	95"	95"	95"	95"	95"	95"	
Overall length	250"	280"	280"	255"	285"	255"	285"	
Passenger compartment	156"	186"	186"	156"	186"	156"	186"	

* All passenger capacities based on minimum options and are subject to a weight calculation.

CHASSIS

	FORD E350 or E450	GM
Wheelbase	138" OR 158"	139" or 159"
Engine	6.0L diesel	6.0L gas/6.6L diesel
Transmission	4-Speed auto w/overdrive	4-Speed auto w/overdrive
GVWR	11,500 or 14,050	12,300
Fuel tank	37 or 55 Gallon	35 Gallon
Brakes	Power w/4-wheel antilock	Power w/4-wheel antilock
Tires	LT225/75R 16E BSW radials	LT225/75R 16E BSW radials
Alternator	130 Amp.	145 Amp.
Bateries	Dual 78 Amp, 750 CCA	One 600 CCA - gas Dual 770 CCA - diesel

BODY

	FORD E350 or E450	GM
Body	Galvanized steel	Galvanized steel
Flooring	1/2" Plywood Black rubber w/ribbed aisle	1/2" Plywood Black rubber w/ribbed aisle
Split sash windows	28" x 28" w/12" opening	28" x 28" w/12" opening
Wrap-around rubrails	Seat and floor level std.	Seat and floor level std.
Warning system	4 Amber, 4 red	4 Amber, 4 red
Interior lights	4 Dome lights	4 Dome lights
Exterior lights	7" Stop/tail/turn 4" Stop/tail/backup	7" Stop/tail/turn 4" Stop/tail/backup
Mirrors	Rearview and crossover	Rearview and crossover
Bumpers	Black wrap-around	Black wrap-around

OPTIONS


Fire blocking upholstery	Kickout windows	Roof escape hatch
Rear heater	Rear in-wall A/C	Safety equipment
Backup alarm	White roof	Interior mirrors
AM/FM/CD radio	PA system	Spare tire
5/8" plywood floor	Colored rubber flooring	Strobe lights
Electric monitors	Crossing control arms	Static roof vent
Vandal lock (emergency door)	Dark tinted windows	Safety seats
Rubrails at window and skirt level	Electric DOD door	

FEATURES



Single piece "wrap-around" rubrails include integral corners and caps for added protection. The bumper design offers increased stability and a new slip-joint under the bumper corner ABS shrouds.

Integrated rear air-conditioning locates unit within the rear bulkhead. This maximizes passenger compartment headroom.



The rear emergency door design has an increased signage area and a 40% increase in upper glass area. Galvanized tubular construction for maximized corrosion resistance and rigidity. Lower window standard on all models.

Optional entrance door with transition panel provides added visibility.



Optional equipment cages are available in a variety of configurations.

Distributor:

415 West 6th Street • South Hutchinson, KS 67505
1.800.533.1850 • Fax: 620.662.3838
www.collinsbuscorp.com

Due to ongoing engineering improvements, Collins reserves the right to make changes without notification.